



Designer Washdown Urinal

SU-7409

Product description

Standard, Vitreous China Washdown Urinal.

Compliances & Certifications



CalGreen



(ADA Compliant, CalGreen Compliant, cUPC Green Certified, EPD, HPD, IAPMO, EPA WaterSense Listed)

Code 1107409

Downloads

- [Model SU-7409-7419 Urinal Installation Instructions.pdf](#)
- [Designer Urinal Brochure.pdf](#)
- [Fixture Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan - Company Overview](#)

Details

- Flush Volume: 0.125-1.0 gpf (1.9-3.8 lpf)
- Flush Volume determined by the Flushometer used with the Fixture
- Nominal Dimensions: 14.125" x 12.625" x 23.125" (359 x 321 x 587mm)
- Flush Method: Washdown

Features

- Designed to maximize and complement Sloan flushometers
- Small size and fully enclosed trapway provide attractive design
- Thorough washdown flushing action
- Vandal resistant stainless steel strainer included
- IAPMO certified to meet or exceed ASME A112.19.2 standards
- Water Sense listed by EPA that qualifies for most rebate programs
- Meets ADA guidelines and ANSI A117.1 requirements when installed accordingly

Plumbing System Requirements

- Maximum Static Pressure: 80 PSI (552 kPa)
- Maximum Flow Rate: 8.5 gpm (32.2 Lpm)

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.

WaterSense compliant when used with a WaterSense compliant flushometer.

[Find a compatible flushometer](#) for this urinal.

